

LS
Multi-speed closed three-phase induction motors
Optional PTO (normally closed thermal protection)
AVAILABILITY TIMES EX WORKS (FRANCE), IN WORKING DAYS

Orders received, within the maximum quantity limit, by the factory on day D before 12:00 pm Central European Time, will have the following Availability.

For products with options, availability will be that of the longest lead-time item, i.e: the product or its options.

If the order is received after 12:00 pm, 1 working day will be added to the stated lead time.

The maximum quantity is per line of order. Above this maximum quantity, please consult your Sales Office.

D**D + 1****D + 2****D + 5****D + 10****Please consult**

2/4 poles 3000-1500 min ⁻¹		ΔT 80 K 400 V	
Type		Rated output power at 50 Hz	IM 1001 (IM B3)
		P _n kW	Code Max. qty
LS 80 L	GV ⁽¹⁾	1.1	4672856
	PV ⁽²⁾	0.25	5
LS 90 SL	GV	1.5	
	PV	0.35	-
LS 90 L	GV	2.2	
	PV	0.6	2
LS 100 L	GV	3	
	PV	0.8	2
LS 112 MU	GV	4.5	
	PV	1.3	2
LS 132 SM	GV	6	
	PV	1.6	1
LS 132 M	GV	9	
	PV	2.5	1

⁽¹⁾ High speed - ⁽²⁾ Low speed

4/8 poles 1500-750 min ⁻¹		ΔT 80 K 400 V	
Type		Rated output power at 50 Hz	IM 1001 (IM B3)
		P _n kW	Code Max. qty
LS 71 M	GV ⁽¹⁾	0.25	3798992
	PV ⁽²⁾	0.06	5
LS 71 M	GV	0.37	
	PV	0.07	
LS 80 L	GV	0.55	
	PV	0.09	2
LS 80 L	GV	0.75	
	PV	0.12	5
LS 90 SL	GV	1.1	
	PV	0.18	-
LS 90 L	GV	1.5	
	PV	0.25	5
LS 100 L	GV	2.2	
	PV	0.37	5
LS 100 L	GV	3	
	PV	0.55	5
LS 112 MU	GV	4	
	PV	0.75	5
LS 132 MU	GV	5.5	
	PV	1.1	3
LS 132 M	GV	7.5	
	PV	1.5	3
LS 160 M	GV	9	
	PV	2.2	2
LS 160 M	GV	11	
	PV	2.8	2
LS 160 L	GV	13	
	PV	3.3	2
LS 160 L	GV	15	
	PV	3.8	2
LS 180 L	GV	18.5	
	PV	4.8	2
LS 180 L	GV	22	
	PV	5.3	-
LS 200 L	GV	30	
	PV	7	1

⁽¹⁾ High speed - ⁽²⁾ Low speed

Your sales office will offer every assistance and consider any enquiry concerning delivery of larger quantities and different delivery dates