



Marine & Offshore

Certificate number: 16598/D3 BV

File number: ACE 04/440/04

Product code: 2572I

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to

Nidec Leroy Somer EPG Angoulême

ANGOULEME cedex 9 - FRANCE

for the type of product

ALTERNATING CURRENT GENERATORS (Power 100kW and over)

LSAM series.

Requirements:

Bureau Veritas Rules for the Classification of Steel Ships, offshore units, naval ships and yachts.
IEC 60034-1 (2010), IEC 60092-301 (1995).

FOR information only

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 28 Jun 2026

For Bureau Veritas Marine & Offshore,

At BV BORDEAUX, on 09 Dec 2022

This certificate was created electronically and is valid without signature

This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

Series LSAM ...Low voltage alternator for generator set – 4 poles

Cooling	Air
Degree of protection	IP 23 and IP 44
Ambient temperature	40°C to 50°C
Frequency	50 Hz and 60 Hz
Speed	1500 RPM and 1800 RPM
Excitation system	AREP with AVR type R... AREP+ with AVR type R... or PMG with AVR type R...or, AVR D510C, D350, D550 or D700
Winding	3 phase winding 6 wires or 12 wires 2/3 pitch
Voltage 50 Hz	220 V to 690 V
Voltage 60 Hz	208 V to 690 V
Insulation class	H
Thermal class	B or F or H
Duty	S1 and S2
Power factor	0,8 (0,8 or 0,9 for LSAM49.3M8)
Mounting	Single bearing or two bearing arrangement
Prime mover	Diesel or gas engine or turbine

Rated power at S1 with degree of protection IP 23 and ambient temperature 45°C *

*The power indicated in these tables can be modified according to ambient temperature and duty type

1.1 Type LSAM 44.3

TYPE	POWER at 50 Hz Thermal class F/H kVA 380/400/415V	POWER at 60 Hz Thermal class F/H kVA 440/450/480	POWER at 50Hz Thermal class F/H kVA 690V	Power at 60Hz Thermal class F/H kVA 690V	Power at 50Hz Thermal Class B kVA 400V
LSAM 44.3S5	/	125	/	/	
LSAM 44.3M6	/	135/147	/	/	
LSAM 44.3M8	135	150/164		129	
LSAM 44.3L10	137/150	169/184	128	140/155	
LSAM 44.3VL13	164/180	191/210	145/160	165/185	144
LSAM 44.3VL14	180/195	210/230	160/170	185/206	

1.2 Type LSAM46.3

TYPE	POWER at 50 Hz Thermal class F/H kVA 380/415V	POWER at 60 Hz Thermal class F/H kVA 440/480V	POWER at 50 Hz Thermal class F/H kVA 690V	POWER at 60 Hz Thermal class F/H kVA 690V
LSAM46.3S2	163/180	191/210	145/160	165/185
LSAM46.3S3	180/195	210/230	160/170	185/206
LSAM46.3S4	202/220	237/261	180/200	213/240
LSAM46.3S5	215/231	250/275	190/210	225/250
LSAM46.3M7	240/261	280/307	216/240	240/270
LSAM46.3M8	253/275	295/324	230/253	255/287
LSAM46.3L10	276/300	314/345	240/270	270/300
LSAM46.3L11	303/332	353/388	256/282	295/330

1.3 Type LSAM 47.2

TYPE	POWER at 50 Hz Thermal class F kVA 380/400/415V	POWER at 50 Hz Thermal class H kVA 380/400/415V	POWER at 60 Hz Thermal class F kVA 440/450V	POWER at 60 Hz Thermal class H kVA 440/450V	POWER at 50 Hz Thermal class F/H kVA 690V	POWER at 60 Hz Thermal class F/H kVA 690V	POWER at 60Hz Thermal class B kVA 450V
LSAM 47.2 VS2	330	365	410	430	320 / 345	402 / 443	/
LSAM 47.2 S4	360	390	445	500	350 / 380	415 / 456	375
LSAM 47.2 S5	390	425	485	531	370 / 400	437 / 480	/
LSAM 47.2 M7	450	500	570	625	435 / 465	520 / 580	/
LSAM 47.2 L9	510	556	594	660	480 / 515	540 / 605	/

1.4 Type LSAM 47.3

TYPE	POWER at 50 Hz Thermal class F kVA 380/400/415V	POWER at 50 Hz Thermal class H kVA 380/400/415V	POWER at 60 Hz Thermal class F kVA 440/480V	POWER at 60 Hz Thermal class H kVA 440/480V	POWER at 50 Hz Thermal class F kVA 690V	POWER at 50 Hz Thermal class H kVA 690V	POWER at 60Hz Thermal class F kVA 690V	POWER at 60Hz Thermal class H kVA 690V
LSAM 47.3 VS3	330	365	410	450	/	/	/	/
LSAM 47.3 S4	375	400	455	500	319	350	415	456
LSAM 47.3 S5	400	450	480	530	364	400	437	480
LSAM 47.3 M7	450	500	561	625	400	450	500	530
LSAM 47.3 M8	475	530	575	630	425	465	515	550
LSAM 47.3 L9	525	590	610	675	480	515	540	605
LSAM 47.3 L10	590	610	681	755	520	565	580	650

1.5 Type LSAM49.3

TYPE	POWER at 50 Hz Thermal class F/H kVA 380/400/415V	POWER at 60 Hz Thermal class F/H kVA 440/480V	POWER at 50 Hz Thermal class F/H kVA 690V	POWER at 60 Hz Thermal class F/H kVA 690V
LSAM49.3S4	590/610	681/755	550/615	625/700
LSAM49.3M6	660/730	760/840	600/680	750/800
LSAM49.3M8*	760/820	850/940	650/700	800/860
LSAM49.3L9	820/910	940/1045	725/800	850/900
LSAM49.3L10	892/971	1031/1146	775/850	900/950

* cos phi at 0.8 or 0.9

1.6 Type LSAM 50.2

TYPE	POWER at 50 Hz Thermal class F/H kVA 380/400/415V	POWER at 60 Hz Thermal class F/H kVA 440/450V	POWER at 50 Hz Thermal class F/H kVA 690V	POWER at 60 Hz Thermal class F/H kVA 690V
LSAM 50.2 M6	1080 / 1195	1300 / 1420	950 / 1030	1090 / 1220
LSAM 50.2 L7	1175 / 1290	1390 / 1550	1030 / 1100	/
LSAM 50.2 L8	1270 / 1400	1520 / 1655	1125 / 1215	1290 / 1440
LSAM 50.2 VL10	1390 / 1540	1670 / 1840	1290 / 1385	1450 / 1625

1.7 Type LSAM52.3

TYPE	POWER at 50 Hz Thermal class F/H kVA 380/415V	POWER at 60 Hz Thermal class F/H kVA 440/480V	POWER at 50 Hz Thermal class F/H kVA 690V	POWER at 60 Hz Thermal class F/H kVA 690V
LSAM52.3S6	1640/1795	1965/2155	1510/1670	-
LSAM52.3S7	1925/2110	2310/2535	1680/1855	2070/2285
LSAM52.3L9	2085/2305	2505/2770	1965/2170	2150/2375
LSAM52.3L12	2210/2445	2655/2930	2140/2365	2550/2815

Options:

Filters on air inlet and air outlet (IP 44).

Winding protections for harsh environments and relative humidity greater than 95%.

Space heaters.

Thermal protection for winding.

Possible inclusion of accessories for paralleling, protection and measurement.

4. APPLICATION / LIMITATION:**4.1 Application / limit of use**

According to BV Rules for the classification of steel ships, offshore units, naval ships and yachts.

- Power decrease of 10% from table in item I when degree of protection IP 44.
- Power decrease of 5% from table in item I when degree of protection IP 23 with air inlet filter.

4.2 - On board installation & Maintenance requirements:

According to BV Rules for the classification of steel ships, offshore units, naval ships and yachts.

*** END OF CERTIFICATE ***